





功能描述:

CFP2 系列单向阀允许油液从 1 流向 2, 同时截止油液反向流动。

技术数据:

工作压力: 350bar
 内泄漏: 5 滴 / 分钟 (350 bar 压力下)
 工作环境温度: -40°C - +120°C (丁晴橡胶密封)
 建议油液清洁度: ISO 17/15/13
 油液: 矿物油, 粘度等级为 VG32, 46, 68
 流量: 见以下性能曲线

最大流量	型号	插孔	A	B	C	安装扭矩
38 L/min	CFP2-08	C08-2	27.0	24.0	12.0	47-54 Nm
60 L/min	CFP2-10	C10-2	32.0	25.4	22.0	74-81 Nm
100 L/min	CFP2-12	C12-2	45.0	32.0	17.0	95-100 Nm
150 L/min	CFP2-16	C16-2	45.0	38.0	16.0	95-100 Nm



CFP2

08

N

005

①

②

③

④

① 产品系列

CFP2 = 单向阀,
锥面密封, 2 通

② 规格

08 = 3/4-16 UNF
 10 = 7/8-14 UNF
 12 = 1-1/16-12 UN
 16 = 1-5/16-12 UN

③ 密封材料

N = 丁晴橡胶
 V = 氟橡胶

④ 开启压力

005 = 5 psi (0.34 bar)
 015 = 15 psi (1.0 bar)
 030 = 30 psi (2.0 bar)
 060 = 60 psi (4.0 bar)
 120 = 120 psi (8.0 bar)
 * 其它开启压力可按需订制